



SIMULATION DEVICE P1

TECHNICAL SPEC'S EG18 ASSAULT SMOKE

Product Specification

Effect:	Smoke	Colour:	As per band on label
Project Debris:	< 1 metre (ash)	Effect Duration:	90s ± 30s
*NEC:	152g Max	**Safety Delay:	2s Approx.
Ignition Type:	Wire Pull	Burn rate:	2g/s (max)

* This is the pyrotechnic content of the device.

** This is the delay time between ignition of the fuse and the effect being produced.

Storage

- Store in accordance with local, regional or national regulations.
- A storage licence(s) maybe required depending on the quantity being stored.
- Store devices in their original transport packaging, reseal opened boxes.
- Store in a cool dry place with relative humidity less than 70%.
- Avoid sub-zero temperatures and temperatures above 75 °C.
- Avoid excessive temperature fluctuations as continuous freezing and thawing will damage the product.

Packing and Transport (weights and sizes are approximate)

Items per Carton:	50
Carton Dimensions:	31 cm x 31 cm x 28 cm
Carton ***NEC:	7.2 Kg (max)
Carton Net Weight:	15.50 Kg (max)
Carton Gross Weight:	17.0 Kg (max)

***This is the Net Explosive Content of outer shipping carton.

Proper shipping name: **Articles Pyrotechnic** for technical purposes

Hazard Class: **1.4**

Compatibility Group: **G**

UN number: **0431**

Packing Group: **II**

Packing Instruction: **135**

DO NOT Send these items through the postal system.

DO NOT take these items on Aircraft or Ferries.

FOR ALL shipping queries, please contact the office.

Hazard Label



Misfire & Disposal

Misfire: Do not return to it or pick up for at least 5 minutes. Soak in a bucket of water to await disposal.

Disposal: Submerge in a bucket of water to allow the water to enter the product. Leave soaking outside in a secure area for a minimum of 48 hours. Dispose of the water waste and the solid waste(s) separately and in accordance with local, regional and national regulations.